

Attachment "B"
Clean Copy of Amended Claims)

81

1. (Four Times Amended) A seatback for an automobile comprising:

a seatback frame comprising:

side frames spaced from each other; and

a cross frame located between the side frames;

a pivot rotatably supported by the seatback frame; and

a headrest member supported by the pivot for rotating coaxially with the pivot and relative to the side frames,

the headrest member comprising:

a headrest mounted on the seatback frame; and

a supporting member including a pressure receiving portion, the supporting member being located between the side frames and supporting the headrest,

wherein the cross frame is located in front of the supporting member for stopping the supporting member from pivotal motion.

15. (Four Times Amended) A seatback for an automobile comprising:

12

a seatback frame including a side frame;

a pivot rotatably supported by the seatback frame;

a headrest member supported by the pivot for rotating coaxially with the pivot and relative to the side frame; and

D1 cont.
a stopper located transversely relative to the side frame and in front of the headrest for stopping the headrest from pivotal motion.

D2 cont.
16. (Thrice Amended) A seatback according to claim 15, wherein the headrest member includes:
a headrest;
a pressure receiving member; and
a supporting member extending between the headrest and the pressure receiving member and supporting the headrest,
wherein the pivot rotatably supports the supporting member.

D3
28. (Thrice Amended) A seatback according to claim 16, wherein the supporting member further comprises:
a holder for fitting the headrest therein.